1140

Tally DASCOM®

Highlights at a glance:

- Compact 9-pin narrow carriage printer

- Up to 400 characters per second

- Ideal for front and back office applications

- Variatey of interfaces

- Long life ribbon

- Small footprint

The Tally Dascom 1140, is a 9 pin, 80 column serial dot matrix printer with USB interfaces as standard. Compact in size, the 1140 is perfect for industrial environments and front and back office applications where space is limited.

With low running costs, high quality output and an easy to use control panel it's ideal for small business, low volume listings and reports, as well as dispatch notes and labels.

In addition to these applications, the 1140 is also well suited to measurement and control systems. Amongst the lowest priced matrix printers available today the 1140 also offers a long life ribbon giving this printer very low running costs.

For draft printing it's considerably less expensive running costs make it a viable alternative to low cost inkjet printers.

Configurations:
- **1140** Standard Product with USB interface
- **1140 Par** With USB and parallel interface
- **1140 Ser** With USB and serial interface

SERIAL MATRIX PRINTERS

MOBILE PRINTERS

FLATBED PRINTERS

THERMAL PRINTERS

CONNECTIVITY

CONSUMABLES

SERVICE

1140

Print Speed	400 cps (Fastest Draft); 300 cps (Draft), 75 cps (NLQ) at 10 cpi
Resolution	up to 144 x 240 dpi
Throughput	290 pages per hour
Character Density	10, 12, 15, 17.1, 20 cpi
Line Density	1, 2, 3, 4, 6, 8 lpi
Printhead Life	400 million strokes
Memory	up to 256 kB
Standard Connectivity	USB 2.0
Optional Connectivity	Parallel IEEE 1284. Serial RS-232C, Ethernet (10/100)
Standard Emulation	IBM ProPrinter2380 Plus, Epson ESC P/2
Fonts	Draft, Quadrato, Courier, HS Draft, OCR-A/B, EAN-8, EAN-13, Interleaved 2 of 5, UPC-A, UPC-E, Code 39, Code 128, POSTNET
Consumables	Ribbon: 9 million characters
Standard Paper Handling	Push tractor and friction
Optional Paper Handling	Roll holder
Number of Copies	1 original + 4 copies
Paper Type	Cut sheets, continuous forms, mulit-part forms
Paper Weight	52 - 100 g/m²
Paper Size	Width: 95 to 267 mm Length: 114 to 362 mm (Cut sheet); 114 to 558 mm (Fanfold)
Physical Weight	5 kg
Physical Size	369 x 283 x 130 mm (W x D x H)
Acoustic	57 dB(A)
Power Voltage	100-230 V - 50/60 Hz
Power Consumption	less then 1,2 Watt Sleep Mode
Temperature	+5° to +35° C; 10% to 80% humidity
Workload	6.000 pages per month
MTBF	12.000 hours
Drivers	Windows XP/Vista/7/8.1 and Server 2003/2008/2012

SERIAL MATRIX PRINTERS
MOBILE PRINTERS
FLATBED PRINTERS
THERMAL PRINTERS